

C18 CDMA module

Delivering seamless mobility to the M2M world.



The Motorola C18 CDMA 1X module enables seamless connectivity for today's fastest-growing M2M applications.

The C18 module delivers high-speed wireless data and voice communication in the CDMA 1X 800/1900 MHz, and 800 MHz AMPS range. It includes aGPS/AFLT capabilities and complies with the FCC E911 Phase II Location Mandate. The C18 module has several optional interface connectors which provides greater flexibility in meeting customer needs.

The C18 module is ideally suited for the telemetry, security, EPOS industries, delivery and hand-held terminal markets.



MOTO2MOTO



Product Highlights:

Dual band Tri mode

- CDMA 1X 800/1900 MHz
- AMPS 800 MHz

CDMA 1 x voice and data

- Packet data max BR 153.6 Kbps
- Differential Audio

C18 CDMA module

Product Specifications

PRODUCT FEATURES

Operating Systems

- CDMA 1X 800/1900 MHz
- AMPS 800 MHz

Physical

- Size: 40.0x 80.2 x 8.7 mm
- Mounting: Four 2.3 mm holes
- Weight: 25 gram

Environmental

- Operating temperature:
-20°C +60°C
- Functional temperature:
-25°C +70°C
- Storage temperature:
-40°C +85°

PERFORMANCE

Operating Voltage

- Voltage: 3.6 - 4.5V DC

Current consumption

- Call: CDMA =740 mA ;
AMPS =940 mA
- Standby: CDMA =5mA; AMPS
=55mA
- Off: <5µA

TX Power

- CDMA: +24 dBm@ RF port
- AMPS: +27.5 dBm@ RF port

Typical RX sensitivity

- Digital <-104 dBm ;
Analog <-116 dBm

INTERFACES

Connectors

- 70 pin 0.5mm pitch board to board
- 36 pin ZIF
- 28 pin DIN
- RF MMCX

SERIAL

- RS232
- USB

DATA FEATURES

CDMA 1X

- Packet Data Max BR 153.6 Kbps

CSD

- Max BR 14.4 Kbps

CDMA Data

- IS707 - Max BR 14.4 Kbps
- IS95B - Max BR 64 Kbps

SMS

- MO / MT Text mode
- MO / MT PDU mode

FAX Class 1

- Class 2 group 3

VOICE FEATURES

- Telephony
- Differential analog audio lines
- Vocoders EVRC/OCELP
- DTMF support
- Audio control: echo cancellation;
noise suppression; side tone;
gain control

SUPPLEMENTARY SERVICE

- USSD phase II
- Call Forwarding
- Call hold; waiting; multiparty
- Missed call indicator
- AOC
- Call barring

EMERGENCY & LOCATION

- FCC E911 Phase II location
mandate using aGPS/AFLT

CONTROL / STATUS INDICATIONS

- Wake up in
- Wake up out

AT COMMAND SET

- IS 707A AT commands
- Motorola proprietary AT
commands

ACCESSORIES

- Firmware data loader
- Data logger
- Developer kit

REGULATORY AND STANDARDS

- IS-98D: Minimum mobile
performance standard, Phase I
and Phase II
- CDMA 2000 R.O
- IS95 A/B Phase I, Phase II
- IS-683A: Over The Air Activation
- TTY compliant
- QS9000 manufacturing



CONTACT

M2M.Sales@motorola.com

For more information check out our website at www.motorola.com/m2m



Motorola reserves the right to change products, accessories and services without prior notice. All information is accurate at press time. MOTOROLA and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. All other product or service names are the property of their respective owners. © Motorola, Inc. 2005